

24V U1-25

U1LiFe™ Series | Data Sheet

inventus™
POWER



Automotive grade cells
from top tier manufacturers



Fast charging
within 2 hours



Long shelf life performance
with Shutdown mode



- **Plug & play lead acid replacement**
- **UL2054 Shock & Vibration + Thermal Propagation Mitigation**
- **Compatible with many off-the-shelf chargers**
- **Increased life cycles up to 10X over Sealed Lead Acid**

Electrical Specifications

Cell Chemistry	LiFePO4
Pack Voltage (Nom/Max)	25.6V / 28.0V
Pack Energy	676Wh (26Ah)
Specific Energy	102Wh/kg
Continuous Power	512W / 20A
Recommended Charge CCCV	12.8A / 28.0V
Peak Power (<10sec)	716W (28A)
Cycle Life (@ 25°C)	3,000 @ 80% DoD

Compatible Inverters

Tripplite	HC150SL HCINT150SL HC120DC
PowerVar	ABCE150

Operational Specifications

Charge Temp	0°C to 40°C
Discharge Temp	-20°C to 60°C
Storage Temp	-40°C to 60°C
Humidity (Operating)	20% to 80%

Mechanical Specifications



BCI Size	U1
Terminal Type (ISO)	M6
Terminal Torque (Nm)	3.1 ± 0.3 Nm
Weight	6.64kg (14.64lbs)
Installation Orientation	Horizontal / Vertical
Ingress Protection Rating	IP51
Case Flammability Rating	Flame Retardant UL94 V-0

Certifications

- UL/CSA62133-2:20
- UL2054
- IEC62133-2:2017
- RoHS
- EMC
- UN/DOT 38.3

Inventus Power reserves the right to make adjustments to this document at any time, without notice or obligation. All data in this publication is for reference use only. Models may vary from shown.

inventuspower.com | info@inventuspower.com | +1 877.423.4242

12V U1-40 2022-08-08

Market Applications



Medical Carts



E-Mobility



Industrial Carts



Request more Info